



# Makina Grease & Lubricants Manufacturing L.L.C.

## Tridon ATF-VI

### Description

Tridon ATF VI is formulated with synthetic base oils and an additive package suitably balanced in order to give the product the properties required by Dexron VI.

This Product guarantees:

- Exceptional low temperature performance.
- Improved thermal and oxidation stability.
- Excellent frictional properties that provides smooth gear shifting at low temperature and help to prevent transmission vibration.
- Exceptional resistance to the formation of sludge and deposits.
- Prolonged life of the fluid.

### Application

- The product Tridon ATF VI is recommended as hydraulic fluid for modern automatic transmissions. The high technology used enables longer transmission life.
- This lubricant has been developed to meet the needs of modern transmission where high efficiency is required. It is a low viscosity formulation that meets the more demanded OEM specification.
- Very good foaming control.
- Excellent parts material compatibility.
- Outstanding film-strength and anti-wear properties which provides a perfect lubrication all over time and protection of the transmission.
- Excellent viscosity stability in operation.

**Caution:** Do not overfill automatic transmissions as this may cause foaming and possible malfunction of the unit. Failure to use specific manufacturer's recommendations with regard to transmission fluid could void the vehicle warranty.

### Typical Characteristics

PROPERTIES	UNITS	TEST METHOD	VALUE
Color			Red
Density @ 15 °C	kg/m <sup>3</sup>	ASTM D-4052	845
Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D-445	30.28
Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D-445	6.054
Viscosity Index		ASTM D-2270	152
Flash Point, COC	°C	ASTM D-92	208
Pour Point	°C	ASTM D-97	-45